



DESCRIPTION

CODE PRODUIT	ID" (pouces)	DI (mm)	WP (barre)	BP (bar)	BR/r (mm)	gramme/mt	mont
BLT-10-004-100	3/16"	4	16	64	60	85	100
BLT-10-005-100	3/16"	5	16	64	80	100	100
BLT-10-6,3-100	1/4"	6,3	16	64	95	115	100
BLT-10-008-100	5/16"	8	16	64	105	140	100
BLT-10-009-100		9	16	64	110	150	100
BLT-10-010-100	3/8"	10	16	64	120	180	100
BLT-10-12,5-100	1/2"	12,5	16	64	140	250	100
BLT-10-016-100	5/8"	16	10	40	180	360	100
BLT-10-019-050	3/4"	19	10	40	220	480	50
BLT-10-022-050		22	10	40	250	580	50
BLT-10-025-050	1"	25	10	40	260	680	50
BLT-10-032-050	1 1/4"	32	10	40	320	900	50
BLT-10-038-050	1 1/2"	38	10	40	440	1100	50
BLT-10-050-050	2"	50	10	40	500	1550	50

NORMES STANDARD	Plage de température	RENK/COULEUR
ISO 1307 TS EN ISO 5774 TYP B - TYP C	 -10°C / +60°C +14°F / +140°F	
SYSTÈME DE GESTION		
ISO 9001 et TS EN ISO/CEI 27001		